

## ROUND SLING

High Tenacity Polyester

We make these products according to EN 1492-1 safety requirement.  
Polyester round sling is a versatile, convenient, and cost-effective way to lift a variety of cargo

Feature :  
Safety factor:7:1  
Better breaking strength than web sling with less weight  
Easy handling and stocking  
Do not damage the lifted body High capacity ,brightly colored High resistance to chemical and oil contamination



Code	Color Code	S.W.L(T)	Working Load Limits								
			Vertical Hitch	Chocker Hitch	Basket Hitch		Two Leg Sling		Three and Four Leg Sling		
					Parallel	$\beta=0^{\circ}-45^{\circ}$	$\beta=45^{\circ}-60^{\circ}$	$\beta=0^{\circ}-45^{\circ}$	$\beta=45^{\circ}-60^{\circ}$	$\beta=0^{\circ}-45^{\circ}$	$\beta=45^{\circ}-60^{\circ}$
			M=1.0	M=0.8	M=2	M=1.4	M=1	M=1.4	M=1	M=2.1	M=1.5
2222011	VIOLET	1	1	0.8	2	1.4	1	1.4	1	2.1	1.5
2222021	GREEN	2	2	1.6	4	2.8	2	2.8	2	4.2	3.0
2222031	YELLOW	3	3	2.4	6	4.2	3	4.2	3	6.3	4.5
2222041	GREY	4	4	3.2	8	5.6	4	5.6	4	8.4	6.0
2222051	RED	5	5	4.0	10	7.0	5	7.0	5	10.5	7.5
2222061	BROWN	6	6	4.8	12	8.4	6	8.4	6	12.6	9.0
2222071	BLUE	8	8	6.4	16	11.2	8	11.2	8	16.8	12.0
2222081	ORANGE	10	10	8.0	20	14.0	10	14.0	10	21.0	15.0
		12	12	9.6	24	16.8	12	16.8	12	25.2	18



Lloyd's Register



ClassNK

