

## TOUGH-LEAD

High Tenacity Polypropylene with Lead Core

Construction: 3-strand

This rope works well in a variety of marine applications requiring durable, rot-proof lines that sink. It can offer good strength and resistance to abrasion and UV light. We can provide leaded ground line in both coils and reels.

**Features:**

Abrasion Resistance: Good  
 Chemical Resistance: Very Good  
 UV Resistance: Good  
 Water Absorption : 0%  
 Wet-dry Strength Ratio: Dry=Wet

**Applications:**

Fishing Line  
 Aquaculture



Dia.		Circ.	Weight		MBL	
mm	inch	inch	kg/100m	lbs/100ft	ton	kN
12	1/2	1-1/2	10.5	7	0.2	1.9
14	9/16	1-3/4	14.3	9.6	0.3	2.6
16	5/8	2	18.8	12.6	0.3	3.2
18	3/4	2-1/4	22.5	15.1	0.4	4
20	13/16	2-1/2	29.5	19.8	0.5	4.8
22	7/8	2-3/4	35	23.5	0.6	5.9
24	1	3	41.3	27.7	0.7	6.9
26	1-1/16	3-1/4	49.5	33.2	0.8	7.9
28	1-1/8	3-1/2	57.5	38.6	0.9	9
30	1-1/4	3-3/4	63.8	42.8	1.1	10.4
32	1-5/16	4	71.3	47.8	1.2	11.7
36	1-1/2	4-1/2	91	61	1.4	13.4
40	1-5/8	5	112.5	75.5	1.8	17.7



Lloyd's Register



ClassNK

